

A301 Plug, Push, and Extend any WiFi Network to a Farther Distance

Wireless N300 Universal Range Extender

The A301 Wireless N300 Universal Range Extender is designed to extend the range of the current wireless network and improve coverage to eliminate "dead spot", giving you the freedom roam anywhere in the house and access Internet. Delivering up to 300Mbps wireless performance, it is ideal for streaming videos and online gaming. The product was specifically designed to be plugged into an electrical outlet, and blends in nicely with any surrounding. It is also provides one Ethernet port for you to connect wired devices like Blu-ray player, gaming console, DVRs, and Internet TV.



Push & Connect

Instantly extend the range of the current wireless network to enjoy increased in-home mobility at a push of WPS button



Easy Setup

Set up in minutes. Just plug, scan and connect. No need to insert a CD or plug in network cable



Optimal Coverage

WiFi signal display helps to locate the best placement spot to achieve the best extended range of the current WiFi network



Wall-plug Design

WiFi signal display helps to locate the best placement spot to achieve the best extended range of the current WiFi network

Specifications

Hardware Features	Wireless Standards	802.11n/g/b, IEEE 802.3/802.3u
	Interface	1*10/100M LAN
	Plug Type	EU、US、AU、UK
	Antenna	External (2)
	Button	Range Extender button reset button
	Power Supply	Input: AC:100~240V; 50/60Hz Output: 5.0V 0.7A
	Product Dimensions (L*W*H)	110mm*55mm*39mm
	LEDs	Power, RE(Range Extender), Signal Strength indicator, LAN
Wireless Features	Wireless Rate	Up to 300Mbps
	Frequency	2.412GHz-2.472GHz
	Wireless Functions	Wireless Radio: Enable/Disable SSID Broadcast: Enable/Disable Channel: 1-11 Domain Login Function
	Wireless Security	Wireless Access Control Wireless Security: Enable/Disable WPA-PSK/WPA2-PSK, WPA-PSK, WPA2-PSK、WEP
Software Features	Wireless Mode	Range Extender mode
Others	Temperature	Operating Temperature: 0℃~40℃ Storage Temperature: -40℃~70℃
	Humidity	Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
	Default Settings	Default Access: http://re.tendacn.com Login Password: admin
	Certification	CE; FCC; RoHS
	Related Products	D301 Wireless N300 ADSL2+ Modem Router F300 Wireless N300 Router W322U Wireless N300 USB Adapter
	Package Contents	Wireless N300 Universal Range Extender Ethernet cable Quick Installation Guide Resources CD

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

No. 34-1 Shilong Road Shiyan Town, Baoan District Shenzhen 518108,China

Phone: (86 755) 2765 7180 Fax:(86 755) 2765 7178

Email: sales@tenda.com.cn support@tenda.com.cn

<http://www.tendacn.com>



© 2013 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.