

Strictly Power

The VP350 is crafted for just three things: Quality, performance and incredible value. This entry-level solution gives you everything you need in a power supply. No twinkly lights or glittery paint jobs – just a 120 mm fan for effective and quiet cooling, dual +12V rails for amazingly stable power, and heavy-duty protection circuitry for peace of mind, no matter how demanding your system. And it comes with all the assurance of Antec's AQ2 Antec Quality 2-year limited warranty. All the features, none of the waste: For builders that are strictly business, the VP350 is strictly power.



> 350

350
WATT
ATX12V V2.3



120MM FAN



EuP 2010

SPECIFICATIONS:

- **350 watts of Continuous Power**
- **ATX12V version 2.3 / EPS12V version 2.91** compliant
- **Dual +12V rails** ensure greater system stability
- **EuP 2010 compliant** assuring efficiency and low standby power consumption
- **120 mm fan** delivers quiet, reliable cooling
- **Heavy-duty protection circuitry on all rails** prevents damage from a variety of dangers
 - Over Current Protection (OCP)
 - Over Voltage Protection (OVP)
 - Short Circuit Protection (SCP)
 - Over Power Protection (OPP)
 - Over Temperature Protection (OTP)
- **Safety:** cUL, FCC, CB, BSMI, Gost-R
- **Net Weight**
 - 3.3 lbs / 1.5 kg
- **Gross Weight**
 - 4 lbs / 1.8 kg
- **Unit Dimensions**
 - 86 mm (H) x 150 mm (W) x 140 mm (D)
 - 3.4" (H) x 5.9" (W) x 5.5" (D)
- **Box Dimensions**
 - 110 mm (H) x 230 mm (W) x 170 mm (D)
 - 4.3" (H) x 9.1" (W) x 6.7" (D)

INPUT:

Voltage:	110 – 125VAC / 220 – 240VAC $\pm$ 10%
Frequency Range:	50Hz – 60Hz
Current	(9A @ 110 VAC, 5A @ 220VAC)
Efficiency	Up to 75%

OUTPUT:

Voltage:	+5V	+3.3V	+12V ₁	+12V ₂	-12V	+5V _{sB}
Max. Load	18A	20A	18A	18A	0.3A	2A
+12V _{1,2} maximum combined output: 336W (28A)						
+3.3V and +5V combined maximum output: 135W						
Total Continuous Power: 350W						

UPC# 0-761345-23530-3 NA
UPC# 0-761345-10531-6 AP